

## CaviBlaster 2570-E

Electric Motor, 29 gpm & 7,250 psi

## **Specifications and Options**

This is the ultimate industrial workhorse for serious cleaning or concrete blasting it effectively strips all types of marine fouling and corrosion to bare metal if needed

## **Accessories Included:**

Feed Hose (15 feet), By-Pass Hose (15 feet),

High Pressure Hose (50 feet), Zero-Thrust Balanced Gun

## **Optional Accessories:**

Aditional pressure hose available in 50 ft or 100 ft sections

Max. Pressure hose length recommended up to 300 ft (100 meters) total

SKID Dimensions		
Length	90" / 228 cm	
Width	61" / 155 cm	
Height	62" / 157 cm	
Weight	5,500 Lbs / 2,500 kg	
Lifting Eyes / FL Slots	YES / YES	

Pump System		
Pressure Pump	HPP H-150	
Туре	Positive Displacement	
Flow Rate	29 gpm / 110 Lpm	
Nozzle Pressure	7,250 psi / 500 Bar	
Hose Diam/Max Lgth	3/4" - 600 ft - 19 mm / 200 m	

	Tools
Tool Type	Zero-Thrust Balanced Gun

Feed System	
Feed Pump	Centrifugal Self-Priming
Lift	20 ft / 6 meter
Flow Rate	62 gpm / 234 Lpm
Power Transm.	Electric Motor

Shipping Dimensions		
Pallet	94x66x68"	6,000 Lbs Gross weight

Fricing and specifications subject to change without notice	* Pricing and specification	ns subject to char	nge without notice
---	-----------------------------	--------------------	--------------------

ng ded

Drive System		
Driver	Electric Motor	
Enclosure	TEFC	
Frame	445T	
Hertz	60/50	
Voltage	460/400 Volts	
Phase	3 Phase	
Output HP/kW	150 HP / 112 kW	
Speed RPM	1,800/1,500 RPM	
Transmission	Direct Drive	
Motor Control	Soft Start	
Control Box	NEMA 4X / IP 56	





CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com